


## NA284T-25-4

### General Purpose Hostile Duty Motor

Energy Efficient – Three Phase – TEFC - AC Motor - Inverter Rated (10:1 VT; 5:1 CT)



### DIMENSIONS – INCHES

A	B	C	D	E	2F1	2F2	G	H	J	O
14.0	11.7	26.6	7.0	5.5	9.5	NA	.80	.53	2.76	14.5
P	R	S	T	U	ES	AA	AB	BA	N-W	Mount
14.0	1.591	.50	2.2	1.875	3.28	1.5	11.3	4.75	4.62	F1

### PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design B - Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor (%)			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT%	LRT%
25	1760	284T	G	92.4	91.7	91.1	85.0	84.0	75.0	74.3	260	180
Amps ( 460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
30.0	182.0	6311	6311	F	TEFC	1.15	372					



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

[www.naemotors.com](http://www.naemotors.com)