

NA143TC-1-4

C-Face General Purpose Hostile Duty Motor

Energy Efficient – Three Phase – TEFC - AC Motor - Inverter Rated (10:1 VT; 5:1 CT)



DIMENSIONS – INCHES

MOUNTING					A	B	C	D	G	J	P	L	BC	AH	AB	AA
E	2F1	2F2	H	BA												
2.75	4	NA	0.34	2.75	7	5.2	12.6	3.5	0.5	1.45	6.95	7.1	+0.12	2.12	6.1	0.75
KEY				KEYSET R	FLANGE					SHAFT EXTENSION						
WIDTH	LENGTH				AK	AJ	BF	BB	BD	N-W	U					
0.188	1.41			0.771	4.5	5.875	3/8-16	0.16	6.5	2.25	0.875					

PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design B - Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor (%)			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT%	LRT%
1	1740	143TC	M	82.5	82.2	81.0	76.0	71.0	58.0	3.02	300	290
Amps (460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
1.5	15.0	6205ZZ	6205ZZ	F	TEFC	1.15	40					



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

www.naemotors.com