

SD1225

SEVERE DUTY – INVERTER RATED (10:1 VT; 5:1 CT)

Energy Efficient – Three Phase – TEFC - AC Motor



DIMENSIONS – INCHES

A	B	C	D	E	2F1	2F2	G	H	J	O
16	15.1	33.3	8	6.25	10.5	12	1.11	0.66	2.75	16
P	R	S	T	U	ES	AA	AB	BA	N-W	Mount
15.8	1.845	0.5	2.5	2.125	3.91	2	14.8	5.25	5.25	F1

PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design B - Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor (%)			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT%	LRT%
25	1185	324T	G	92.4	93.4	92.9	0.835	0.826	0.746	110.80	233	200
Amps (460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
30.6	177.0	6312	6312	F	TEFC	1.15	589					





50Hz AND 60Hz DATA FOR 3 PHASE AC INDUCTION MOTOR AS IT APPEARS ON THE NAMEPLATE.

SEVERE DUTY – INVERTER RATED (10:1 VT; 5:1 CT)

CAT. NO: H1225		FRAME: 324T		ENCL: TEFC		PHASE: 3	
SHAFT END BRG: 6312				OPP/END BRG: 6312			
MAX. AMB: 40° C		INS CLASS: F		RATING: CONT.		MOTOR WEIGHT: 589LBS	
USABLE ON 208V 60HZ AT: 67.7 MAX. AMPS						SER:	
60 HERTZ DATA	HP: 25 RPM: 1185			HP: 25 RPM: 980			50 HERTZ DATA
	VOLTAGE: 230/460V			VOLTAGE: 190/380V			
	F. L. AMPS: 61.2/30.6			F. L. AMPS: 72.2/36.1			
	S.F. AMPS: 72.6/36.3			S.F. AMPS: 72.2/36.1			
	S.F. 1.15	DESIGN: B	CODE: G	S.F. 1.0	DESIGN:	CODE: H	
	NEMA NOM. EFF: 92.4%			NEMA NOM. EFF: 90.2%			
	NOM. P. F.: 0.835			NOM. P. F.: 0.863			
	NEMA MIN. EFF.: 90.2%			NEMA MIN. EFF.: 88.5%			
	MAX. KVAR: 9.80			MAX. KVAR: 6.48			

Note: F.L. = Full Load P.F. = Power Factor S.F. = Service Factor



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632
Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546
www.northamericanelectric-inc.com