

## SD1850

### SEVERE DUTY – INVERTER RATED (10:1 VT; 5:1 CT)

Energy Efficient – Three Phase – TEFC - AC Motor



#### DIMENSIONS – INCHES

A	B	C	D	E	2F1	2F2	G	H	J	O
16	15.1	33.3	8	6.25	10.5	12	1.11	0.66	2.75	16
P	R	S	T	U	ES	AA	AB	BA	N-W	Mount
15.8	1.845	0.5	2.5	2.125	3.91	2	14.8	5.25	5.25	F1

#### PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design B - Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor (%)			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT%	LRT%
50	1770	326T	G	93.4	94.6	94.3	0.908	0.894	0.835	148.36	235	200
Amps ( 460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
55.0	332.8	6312	6312	F	TEFC	1.15	706					





**50Hz AND 60Hz DATA FOR 3 PHASE AC INDUCTION MOTOR AS IT APPEARS ON THE NAMEPLATE.**

**SEVERE DUTY – INVERTER RATED (10:1 VT; 5:1 CT)**

CAT. NO: H1850		FRAME: 326T		ENCL: TEFC		PHASE: 3	
SHAFT END BRG: 6312				OPP/END BRG: 6312			
MAX. AMB: 40° C		INS CLASS: F		RATING: CONT.		MOTOR WEIGHT: 706LBS	
USABLE ON 208V 60HZ AT: 124.6 MAX. AMPS						SER:	
60 HERTZ DATA	HP: 50 RPM: 1770			HP: 50 RPM: 1470			50 HERTZ DATA
	VOLTAGE: 230/460V			VOLTAGE: 190/380V			
	F. L. AMPS: 110.0/55.0			F. L. AMPS: 136.4/68.2			
	S.F. AMPS: 127.6/63.8			S.F. AMPS: 136.4/68.2			
	S.F. 1.15	DESIGN: B	CODE: G	S.F. 1.0	DESIGN:	CODE: H	
	NEMA NOM. EFF: 93.4%			NEMA NOM. EFF: 91.7%			
	NOM. P. F.: 0.908			NOM. P. F.: 0.899			
	NEMA MIN. EFF.: 91.7%			NEMA MIN. EFF.: 90.2%			
	MAX. KVAR: 11.1			MAX. KVAR: 9.30			

**Note: F.L. = Full Load      P.F. = Power Factor      S.F. = Service Factor**



**North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632**  
**Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546**  
[www.northamericanelectric-inc.com](http://www.northamericanelectric-inc.com)