

SD3640

SEVERE DUTY – INVERTER RATED (10:1 VT; 5:1 CT)

Energy Efficient – Three Phase – TEFC - AC Motor



DIMENSIONS – INCHES

A	B	C	D	E	2F1	2F2	G	H	J	O
16	15.1	31.8	8	6.25	10.5	12	1.11	0.66	2.75	16
P	R	S	T	U	ES	AA	AB	BA	N-W	Mount
15.8	1.591	0.5	2.5	1.875	2.03	2	14.8	5.25	3.75	F1

PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design B - Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor (%)			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT%	LRT%
40	3560	324TS	G	92.0	92.8	92.5	0.893	0.904	0.856	59.01	234	167
Amps (460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
46.0	259.3	6312	6312	F	TEFC	1.15	675					



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

www.northamericanelectric-inc.com



50Hz AND 60Hz DATA FOR 3 PHASE AC INDUCTION MOTOR AS IT APPEARS ON THE NAMEPLATE.

SEVERE DUTY – INVERTER RATED (10:1 VT; 5:1 CT)

CAT. NO: H3640		FRAME: 324TS		ENCL: TEFC		PHASE: 3	
SHAFT END BRG: 6312				OPP/END BRG: 6312			
MAX. AMB: 40° C		INS CLASS: F		RATING: CONT.		MOTOR WEIGHT: 675LBS	
USABLE ON 208V 60HZ AT: 101.7 MAX. AMPS						SER:	
60 HERTZ DATA	HP: 40 RPM: 3560			HP: 40 RPM: 2950			50 HERTZ DATA
	VOLTAGE: 230/460V			VOLTAGE: 190/380V			
	F. L. AMPS: 92.0/46.0			F. L. AMPS: 110.6/55.3			
	S.F. AMPS: 106.6/53.3			S.F. AMPS: 110.6/55.3			
	S.F. 1.15	DESIGN: B	CODE: G	S.F. 1.0	DESIGN:	CODE: H	
	NEMA NOM. EFF: 92.0%			NEMA NOM. EFF: 90.2%			
	NOM. P. F.: 0.893			NOM. P. F.: 0.914			
	NEMA MIN. EFF.: 90.2%			NEMA MIN. EFF.: 88.5%			
	MAX. KVAR: 7.49			MAX. KVAR: 7.35			

Note: F.L. = Full Load P.F. = Power Factor S.F. = Service Factor



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632
Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546
www.northamericanelectric-inc.com