


PE182TC-3-2

C-FACE PREMIUM EFFICIENT / INVERTER DUTY MOTOR

Minimum Guaranteed Full Load Efficiency =84.0% - Inverter Duty (20:1 Variable Torque; 10:1 Constant Torque)



DIMENSIONS – INCHES

MOUNTING					A	B	C	D	G	J	P	L	BC	AH	AB	AA
E	2F1	2F2	H	BA												
3.75	4.5	NA	0.41	3.5	9.5	6.3	15.1	4.5	0.7	2.04	8.70	10.7	+0.12	2.62	7.5	0.75
KEY				KEYSET R	FLANGE				SHAFT EXTENSION							
WIDTH	LENGTH				AK	AJ	BF	BB	BD	N-W	U					
0.25	1.78			0.986	8.5	7.25	1/2-13	0.25	9	2.75	1.125					

PERFORMANCE DATA

Three Phase – TEFC – AC Motor – 60Hz - 208-230/460V – NEMA Design B - Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor (%)			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT%	LRT%
3	3510	182TC	K	86.5	86.6	86.1	89.0	87.0	78.0	4.49	330	200
Amps (460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
3.7	32.0	6306ZZ	6306ZZ	F	TEFC	1.15	90					