


XP1810C

C-Face General Purpose Explosion Proof Motors

Class I, Division I, Groups C & D and Class II, Division I, Groups E, F and G - Operating Temperature Code: T3C



DIMENSIONS – INCHES

MOUNTING					A	B	C	D	G	J	P	L	BC	AH	AB	AA
E	2F1	2F2	H	BA												
4.25	5.5	7	0.4	4.25	10.5	8.7	20.3	5.25	0.8	2.4	11.4	12.5	+0.25	3.12	10	1
KEY				KEYSET R	FLANGE				SHAFT EXTENSION							
WIDTH		LENGTH	AK		AJ	BF	BB	BD	N-W	U						
0.312		2.41		1.201	8.5	7.3	1/2-13	0.25	9	3.38	1.375					

PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design B - Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT	LRT
10	1765	215TC	H	89.5	90.8	90.2	0.822	0.826	0.746	29.76	61.7	91.2
Amps (460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
12.8	81	6308-ZZ	6308-ZZ	F	TEFC	1.15	273					



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

www.naemotors.com



50Hz AND 60Hz DATA FOR 3 PHASE AC INDUCTION MOTOR AS IT APPEARS ON THE NAMEPLATE.

XP1810C

CAT. NO: XP1810C		FRAME: 215TC		ENCL: TEFC		PHASE: 3	
SHAFT END BRG: 6308-ZZ				OPP/END BRG: 6308-ZZ			
MAX. AMB: 40° C		INS CLASS: F		RATING: CONT.		MOTOR WEIGHT: 273LBS	
USABLE ON 208V 60HZ AT: 28.3 MAX. AMPS						SER:	
DIVISION I, CLASS I, GROUPS C & D CLASS II, GROUPS E, F & G						OP TEMP CODE: T3C	
60 HERTZ DATA	HP: 10 RPM: 1765			HP: 10 RPM: 1450			50 HERTZ DATA
	VOLTAGE: 230/460V			VOLTAGE: 190/380V			
	F. L. AMPS: 25.6/12.8			F. L. AMPS: 29.8/14.9			
	S.F. AMPS: 29.2/14.6			S.F. AMPS: 29.8/14.9			
	S.F. 1.15	DESIGN: B	CODE: H	S.F. 1.0	DESIGN:	CODE: H	
	NEMA NOM. EFF: 89.5%			NEMA NOM. EFF: 88.5%			
	NOM. P. F.: 0.822			NOM. P. F.: 0.864			
	NEMA MIN. EFF.: 87.5%			NEMA MIN. EFF.: 86.5%			
	MAX. KVAR: 4.04			MAX. KVAR: 2.73			

Note: F.L. = Full Load P.F. = Power Factor S.F. = Service Factor



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

www.naemotors.com