


XP36125C

C-Face General Purpose Explosion Proof Motors

Class I, Division I, Groups C & D and Class II, Division I, Groups E, F and G - Operating Temperature Code: T3C



DIMENSIONS – INCHES

MOUNTING					A	B	C	D	G	J	P	L	BC	AH	AB	AA
E	2F1	2F2	H	BA												
9	14.5	16.5	0.8	7.5	22	22	42.1	11	1.4	3.7	24	27	+0.25	4.5	19.7	3
KEY			KEYSET R	FLANGE				SHAFT EXTENSION								
WIDTH	LENGTH			AK	AJ	BF	BB	BD	N-W	U						
0.625	3.03		2.021	16	14	5/8-11	0.25	18	4.75	2.375						

PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design B - Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT	LRT
125	3580	445TSC	G	94.5	94.6	94.3	89.1	89.0	85.3	177	371.7	194
Amps (460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
134.2	648.2	6314	6314	F	TEFC	1.15	1723					



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

www.naemotors.com



50Hz AND 60Hz DATA FOR 3 PHASE AC INDUCTION MOTOR AS IT APPEARS ON THE NAMEPLATE.

XP36125C

CAT. NO: XP36125C		FRAME: 445TSC		ENCL: TEFC		PHASE: 3	
SHAFT END BRG: 6314				OPP/END BRG: 6314			
MAX. AMB: 40° C		INS CLASS: F		RATING: CONT.		MOTOR WEIGHT: 1723 LBS	
USABLE ON 208V 60HZ AT: MAX. AMPS						SER:	
DIVISION I, CLASS I, GROUPS C & D CLASS II, GROUPS E, F & G						OP TEMP CODE: T3C	
60 HERTZ DATA	HP: 125 RPM: 3580			HP: 125 RPM: 2970			50 HERTZ DATA
	VOLTAGE: 460V			VOLTAGE: 380V			
	F. L. AMPS: 134.2			F. L. AMPS: 162.5			
	S.F. AMPS: 154.3			S.F. AMPS: 162.5			
	S.F. 1.15	DESIGN: B	CODE: G	S.F. 1.0	DESIGN:	CODE: H	
	NEMA NOM. EFF: 94.5%			NEMA NOM. EFF: 93.6%			
	NOM. P. F.: 0.891			NOM. P. F.: 0.899			
	NEMA MIN. EFF.: 93.6%			NEMA MIN. EFF.: 92.4%			
	MAX. KVAR: 25.9			MAX. KVAR: 21.9			

Note: F.L. = Full Load P.F. = Power Factor S.F. = Service Factor



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

www.naemotors.com