


# XP3620C

## C-Face General Purpose Explosion Proof Motors

Class I, Division I, Groups C & D and Class II, Division I, Groups E, F and G - Operating Temperature Code: T3C



### DIMENSIONS – INCHES

MOUNTING					A	B	C	D	G	J	P	L	BC	AH	AB	AA
E	2F1	2F2	H	BA												
5	8.25	10	0.5	4.75	12.5	12.5	26.2	6.25	0.9	2.8	14.1	15.8	+0.25	3.75	13.6	1.25
KEY			KEYSET R	FLANGE				SHAFT EXTENSION								
WIDTH	LENGTH			AK	AJ	BF	BB	BD	N-W	U						
0.375	2.91		1.416	8.5	7.3	1/2-13	0.25	10	4	1.625						

### PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design B - Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT	LRT
20	3520	256TC	G	90.2	92.0	92.0	0.896	0.914	0.866	29.84	61.3	40.4
Amps ( 460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
23.3	145	6309	6309	F	TEFC	1.15	429					



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

[www.naemotors.com](http://www.naemotors.com)



**50Hz AND 60Hz DATA FOR 3 PHASE AC INDUCTION MOTOR AS IT APPEARS ON THE NAMEPLATE.**

## **XP3620C**

CAT. NO: XP3620C		FRAME: 256TC		ENCL: TEFC		PHASE: 3	
SHAFT END BRG: 6309				OPP/END BRG: 6309			
MAX. AMB: 40° C		INS CLASS: F		RATING: CONT.		MOTOR WEIGHT: 429LBS	
USABLE ON 208V 60HZ AT: 182.7 MAX. AMPS						SER:	
DIVISION I, CLASS I, GROUPS C & D CLASS II, GROUPS E, F & G						OP TEMP CODE: T3C	
60 HERTZ DATA	HP: 20 RPM: 3520			HP: 20 RPM: 2910			50 HERTZ DATA
	VOLTAGE: 230/460V			VOLTAGE: 190/380V			
	F. L. AMPS: 46.6/23.3			F. L. AMPS: 55.6/27.8			
	S.F. AMPS: 53.8/26.9			S.F. AMPS: 55.6/27.8			
	S.F. 1.15	DESIGN: B	CODE: G	S.F. 1.0	DESIGN:	CODE: H	
	NEMA NOM. EFF: 90.2%			NEMA NOM. EFF: 88.5%			
	NOM. P. F.: 0.896			NOM. P. F.: 0.926			
	NEMA MIN. EFF.: 88.5%			NEMA MIN. EFF.: 86.5%			
	MAX. KVAR: 4.73			MAX. KVAR: 3.67			

**Note: F.L. = Full Load      P.F. = Power Factor      S.F. = Service Factor**



**North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632**

**Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546**

[www.naemotors.com](http://www.naemotors.com)