

## XP36250

### General Purpose Explosion Proof Motor

Class I, Division I, Groups C & D and Class II, Division I, Groups E, F and G - Operating Temperature Code: T3C



#### DIMENSIONS – INCHES

A	B	C	D	E	2F1	2F2	G	H	J	O
22	31	42.1	11	9.0	20.0	25.0	1.4	0.81	3.7	23.5
P	R	S	T	U	ES	AA	AB	BA	N-W	Mount
24	2.021	0.625	4.25	2.375	3.03	3	21.3	7.5	4.75	F1

#### PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design B – Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT	LRT
250	3580	449TS	G	95.4	95.6	95.4	88.7	90.7	87.7	364	691.6	436.8
Amps ( 460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
274.1	1395.2	6314	6314	F	TEFC	1.15	2350					



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

[www.naemotors.com](http://www.naemotors.com)



**50Hz AND 60Hz DATA FOR 3 PHASE AC INDUCTION MOTOR AS IT APPEARS ON THE NAMEPLATE.**

**XP36250**

CAT. NO: XP36250		FRAME: 449TS		ENCL: TEFC		PHASE: 3	
SHAFT END BRG: 6314				OPP/END BRG: 6314			
MAX. AMB: 40° C		INS CLASS: F		RATING: CONT.		MOTOR WEIGHT: 2350 LBS	
USABLE ON 208V 60HZ AT: MAX. AMPS						SER:	
DIVISION I, CLASS I, GROUPS C & D CLASS II, GROUPS E, F & G						OP TEMP CODE: T3C	
60 HERTZ DATA	HP: 250 RPM: 3580			HP: 250 RPM: 2970			50 HERTZ DATA
	VOLTAGE: 460V			VOLTAGE: 380V			
	F. L. AMPS: 274.1			F. L. AMPS: 330.1			
	S.F. AMPS: 315.2			S.F. AMPS: 330.1			
	S.F. 1.15	DESIGN: B	CODE: G	S.F. 1.0	DESIGN:	CODE: H	
	NEMA NOM. EFF: 95.4%			NEMA NOM. EFF: 94.5%			
	NOM. P. F.: 0.887			NOM. P. F.: 0.901			
	NEMA MIN. EFF.: 94.5%			NEMA MIN. EFF.: 93.6%			
	MAX. KVAR: 45.1			MAX. KVAR: 37.8			

Note: F.L. = Full Load P.F. = Power Factor S.F. = Service Factor



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632  
 Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546  
[www.naemotors.com](http://www.naemotors.com)