

NA256T-10-6C

Special Purpose Crusher Duty Motor

Energy Efficient – Three Phase – TEFC - AC Motor - Inverter Rated (10:1 VT; 5:1 CT)



DIMENSIONS – INCHES

| | | | | | | | | | | |
|------|-------|------|------|-------|------|------|------|------|------|-------|
| A | B | C | D | E | 2F1 | 2F2 | G | H | J | O |
| 13.0 | 12.2 | 25.0 | 6.25 | 5.0 | 8.25 | 10.0 | 0.8 | .53 | 2.87 | 13.0 |
| P | R | S | T | U | ES | AA | AB | BA | N-W | Mount |
| 12.4 | 1.416 | .375 | 2.2 | 1.625 | 2.91 | 1.25 | 10.1 | 4.25 | 4.0 | F1 |

PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design C - Max. Ambient: 40° C

| HP | Speed | Frame | NEMA Code | Efficiency (%) | | | Power Factor (%) | | | Torque (ft-lb) | | |
|--------------|-------|------------|-------------|------------------|----------------|----------------|------------------|------|------|----------------|------|------|
| | | | | 100% | 75% | 50% | 100% | 75% | 50% | FLT | BDT% | LRT% |
| 10 | 1165 | 256T | H | 87.5 | 87.8 | 87.2 | 79.0 | 67.0 | 59.8 | 44.9 | 240 | 230 |
| Amps (460V) | | DE Bearing | ODE Bearing | Insulation Class | Enclosure Type | Service Factor | Weight (lbs) | | | | | |
| FLA | LRA | | | | | | | | | | | |
| 13.5 | 81.0 | 6309 | 6309 | F | TEFC | 1.15 | 260 | | | | | |



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

www.naemotors.com