


NA364T-40-6C

Special Purpose Crusher Duty Motor

Energy Efficient – Three Phase – TEFC - AC Motor - Inverter Rated (10:1 VT; 5:1 CT)



DIMENSIONS – INCHES

A	B	C	D	E	2F1	2F2	G	H	J	O
17.1	14.4	32.5	9.0	7.0	11.25	NA	1.1	.66	2.953	18.1
P	R	S	T	U	ES	AA	AB	BA	N-W	Mount
17.6	2.021	.625	2.6	2.375	4.28	3.0	14.6	5.88	5.88	F1

PERFORMANCE DATA

Three Phase – 60Hz - 208-230/460V – NEMA Design C - Max. Ambient: 40° C

HP	Speed	Frame	NEMA Code	Efficiency (%)			Power Factor (%)			Torque (ft-lb)		
				100%	75%	50%	100%	75%	50%	FLT	BDT%	LRT%
40	1180	364T	G	91.7	91.6	91.1	86.0	78.0	76.0	178	215	200
Amps (460V)		DE Bearing	ODE Bearing	Insulation Class	Enclosure Type	Service Factor	Weight (lbs)					
FLA	LRA											
47.0	290	6313	6313	F	TEFC	1.15	672					



North American Electric, Inc. 350 Vaiden Drive, Hernando, MS 38632

Toll Free: 1-800-884-0405 Phone: 662-429-8049 Fax: 662-429-8546

www.naemotors.com